

---

## Device Summary Report

---

### 1. Conformance

**GSRN No.** : 950110126000000223  
**Product Name** : Higgs IC  
**Trade Mark** : N/A  
**Product ID** : N/A  
**Manufacturer** : Alien Technology Corporation  
**Client** : Alien Technology Corporation  
**Standard(s)** : EPCglobal Class-1 Generation-2 UHF Protocol V1.0.9. for Communications at 860MHz to 960 MHz and EPCglobal Radio Frequency Identity Protocols Class-1 Generation-2 UHF RFID Conformance Requirements, Version 1.0.3

Tag IC Features	
Frequency Band	European and North American
Frequency Range	860- 960 MHz
Backscatter Modulation Type	PSK
Support FHSS	N/A
Environment	N/A

## 2. Interoperability

### IC

Name/GSRN of Certified IC	Higgs IC 950110126000000223
Tag Used(model #)	Squiggle ALN-9540
Frequency Bands Tested	862-870 MHz <input checked="" type="checkbox"/> 902 – 928 MHz <input checked="" type="checkbox"/> 950 – 956 MHz <input type="checkbox"/>
*Tested Range:	1 meter
Notes	Tag configurations that utilize the identical certified IC may be as interoperable as the tested tag. See tag manufacturer for selection of tags for this IC.

IC – Integrated Circuit

\* The distance between the reader antenna and tag used for testing

Backscatter Encoding	M	Backscatter Data Rate (kbps)	Tari (µs)		
			6.25 – 12.5	12.5 – 18.75	18.75 – 25
FM0	1	640 – 320	Mod: PR PIE:2:1 DR:64/3 Funct: P Sirit INfinity 510 RFID Reader		
		320 -256			
		256 – 160			
		160 – 40			
Subcarrier	2	320 – 128			
		128 – 20			
	4	160 – 64			
		64 – 10	Mod: DS PIE:1.5:1 DR:8 Funct: P Sirit INfinity 510 RFID Reader		Mod:PR PIE:2:1 DR:64/3 Funct: P Impinj Speedway RFID Reader
		80 – 32	Mod: PR PIE:2:1 DR:64/3 Funct: P Sirit INfinity 510 RFID Reader		
		32 – 5			

**Appendix: Keys**

DS	DSB-ASK
SS	SSB-ASK
PR	PR-ASK
X:1	PIE ratio

**Optional Gen 2 functionality indicated under Funct:**

- P Access passwords supported
- U User memory supported
- WT Write-able TID supported