
Device Summary Report

1. Conformance

GSRN No. : 950110126000000797
Product Name : Monza 2 Gen2 IC
Trade Mark : N/A
Product ID : N/A
Manufacturer : Impinj, Inc.
Client : Impinj, Inc.
Standard(s) : EPCglobal Class-1 Generation-2 UHF Protocol V1.0.9. for Communications at 860MHz to 960 MHz and EPCglobal Radio Frequency Identity Protocols Class-1 Generation-2 UHF RFID Conformance Requirements, Version 1.0.4

Tag Conformance Badge	
Frequency Range	860 - 960 MHz
Backscatter Modulation Type	ASK
Temperature range	-40C to +65C
Optional Command Support	Access, BlockWrite

2. Interoperability

IC

Name/GSRN of Certified IC	Monza 2 IC 950110126000000797
Tag Used(model #)	Monza 2 Tag
Frequency Bands Tested	862-870 MHz <input checked="" type="checkbox"/> 902 – 928 MHz <input checked="" type="checkbox"/> 950 – 956 MHz <input type="checkbox"/>
*Tested Range:	1 meter
Notes	Tag configurations that utilize the identical certified IC may be as interoperable as the tested tag. See tag manufacturer for selection of tags for this IC.

IC – Integrated Circuit

* The distance between the reader antenna and tag used for testing

Backscatter Encoding	M	Backscatter Data Rate (kbps)	Tari (µs)			
			6.25 – 12.5	12.5 – 18.75	18.75 – 25	
FM0	1	640 – 320	Mod: PR PIE:2:1 DR:64/3 Funct: P Sirit INfinity 510 RFID Reader			
		320 -256				
		256 – 160				
		160 – 40				
Subcarrier	2	320 – 128				
		128 – 20				
	4	160 – 64				
		64 – 10	Mod: DS PIE:1.5:1 DR:8 Funct: P Sirit INfinity 510 RFID Reader		Mod:PR PIE:2:1 DR:64/3 Funct: P Impinj Speedway RFID Reader	
		8	80 – 32	Mod: PR PIE:2:1 DR:64/3 Funct: P Sirit INfinity 510 RFID Reader		
			32 – 5			

Appendix: Keys

DS	DSB-ASK
SS	SSB-ASK
PR	PR-ASK
X:1	PIE ratio

Optional Gen 2 functionality indicated under Funct:

- P Access passwords supported
- U User memory supported
- WT Write-able TID supported